









LEGAL DESCRIPTION

WHEREAS, DFWTX DEVELOPMENT, INC., acting by and through the undersigned, it's duly authorized agent, is the sole owner of an 58.801 acre tract of land located in the Seth M. Blair Survey Abstract No. 72 and Cresanto Vela Survey Abstract No. 851. City of Mansfield, Johnson County, and recorded in Instrument No. 2022-22320. Deed Records, Johnson County, Texas, being more particularly described as follows:

BEGINNING at a found 1/2 inch iron rod with a cap stamped "GRAHAM ASSOC INC" (GAI), being in the existing public east right-of-way line of U.S. Highway No. 287 (Variable Width Right-Of-Way) and being in the west line of said 2021 South Pointe Holdings LTD, tract and being the south corner of a tract of land conveyed to Texas Health Resources as recorded in Instrument No. 2017-27224. Deed Records, Johnson County, Texas:

THENCE North 12°23'47" East, along the southeast line of said Texas Health Resources tract, a distance of 190.03 feet to a set 1/2 inch iron rod with a "GAI" cap, being the southwest corner of Lot 1, Block 1, Southpointe Phase 4, as recorded int Instrument No. 2020-99, Drawer K, Plat Records, Johnson County, Texas;

THENCE South 77°36'13" East, leaving said southeast line, along the south line of said Southpointe Phase 4, a distance of 160.92 feet to a set 1/2 inch iron rod with a "GAI" cap, being in the west line of Lot 1X. Block 2, of said Southpointe Phase 4, for the beginning of a non-tangent curve to the left having a radius of 200.00 feet, a central angle of 1°44'44", and a long chord which bears South 06°01'19" West, 6.09 feet:

THENCE along said non-tangent curve to the left, along said west line and continuing along said south line, an arc length of 6.09 feet to a set 1/2 inch iron rod with a "GAI" cap, being the southwest corner of said Lot 1X:

THENCE South 77°27'16" East, continuing along said south line, a distance of 498.24 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE North 12°32'44" East, a distance of 53.18 feet to a set 1/2 inch iron rod with a "GAI" cap, being in the south line of Lot 1X. Block 20. of said Southpointe Phase 4:

THENCE South 77°27'16" East, along the south line of said Lot 1X. Block 20, a distance of 16.02 feet to a set 1/2 inch iron rod with a "GAI" cap, being in the existing south right-of-way line of Bluff Creek Drive (being a 50 foot right-of-way), for the beginning of a non-tangent curve to the left having a radius of 50.00 feet, a central angle of 124°09'05", and a long chord which bears South 61°08'48" East. 88.36 feet:

THENCE along said non-tangent curve to the left, along said existing south right-of-way line and the south line of said Southpointe Phase 4, being a common line, an arc length of 108.34 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE South 77°38'58" East, continuing along said common line, a distance of 138.44 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a tangent curve to the left having a radius of 775.00 feet, a central angle of 6°34'54", and a long chord which bears South 80°56'25" East, 88.98 feet:

THENCE along said tangent curve to the left, an arc length of 89.03 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE South 84°13'52" East, a distance of 135.82 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 39°13'52" East, a distance of 14.14 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 84°13'52" East, a distance of 70.00 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 05°46'08" West, leaving said common line, a distance of 63.73 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a tangent curve to the right having a radius of 510.00 feet, a central angle of 22°44'39", and a long chord which bears South 17°08'28" West, 201.12 feet;

THENCE along said tangent curve to the right, an arc length of 26.28 feet passing the northwest corner of Lot 1. Block 1. MISD-ALMA MARTINEZ INTERMEDIATE SCHOOL ADDITION, as recorded in Volume 11, Page 714, Drawer J, Plat Records, Johnson County, Texas, continuing on for a total arc length of 202.45 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 28°30'47" West, along the northwest line of said Lot 1, a distance of 101.05 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a tangent curve to the right having a radius of 510.00 feet, a central angle of 9°04'10", and a long chord which bears South 33°02'52" West, 80.64 feet:

THENCE along said tangent curve to the right, and continuing along said northwest line, an arc length of 80.73 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 37°34'57" West, continuing along said northwest line, a distance of 113.79 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 07°25'03" East, continuing along said northwest line, a distance of 14.14 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 52°25'03" East, along the southwest line of said Lot 1. a distance of 254.73 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a tangent curve to the left having a radius of 2,229.79 feet, a central angle of 3°10'44", and a long chord which bears South 54°00'25" East. 123.70 feet:

THENCE along said tangent curve to the left, and continuing along said southwest line, an arc length of 123.71 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 55°35'47" East, continuing along said southwest line, a distance of 487.43 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a tangent curve to the right having a radius of 580.00 feet, a central angle of 05°23'47", and a long chord which bears South 52°53'25" East, 54.61 feet:

THENCE along said tangent curve to the right and continuing along said southwest line, an arc length of 54.63 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 40°48'35" West, leaving said southwest line, a distance of 60.01 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE South 06°00'14" East, a distance of 13.74 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE South 49°07'16" East, a distance of 60.00 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE North 40°52'44" East, a distance of 246.30 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE North 85°52'44" East, a distance of 14.14 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE North 40°52'44" East, a distance of 50.00 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE North 04°07'16" East, a distance of 14.14 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE North 40°52'44" East, a distance of 593.25 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a tangent curve to the left having a radius of 4,470.00 feet, a central angle of 00°56'05", and a long chord which bears North 41°20'47" East, 72.93 feet;

THENCE along said tangent curve to the left, an arc length of 72.93 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a reverse curve to the right having a radius of 25.40 feet, a central angle of 102°12'33", and a long chord which bears South 87°05'01" East, 39.54 feet;

THENCE along said reverse curve to the right, an arc length of 45.31 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE South 35.58.47" East, a distance of 426.87 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a tangent curve to the left having a radius of 2,040.00 feet, a central angle of 01°36'21", and a long chord which bears South 36°46'57" East, 57.17 feet;

THENCE along said tangent curve to the left, an arc length of 57.17 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 06.53.35" West, a distance of 14.14 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 38°29'16" East, a distance of 50.07 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 84°00'31" East, a distance of 14.24 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a non-tangent curve to the right having a radius of 2,040 feet, a central angle of 00°26'20", and a long chord which bears South 39°46'14" East, 15.63 feet;

THENCE along said non-tangent curve to the left, an arc length of 15.63 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE South 38°59'24" East, a distance of 449.43 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 07°12'16" West, a distance of 13.59 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 39°59'05" East, a distance of 70.23 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a non-tangent curve to the right having a radius of 610.00 feet, a central angle of 2°26'32", and a long chord which bears South 55°35'09" West, 26.00 feet;

THENCE along said non-tangent curve to the right, an arc length of 26.00 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE South 56°48'25" West, a distance of 87.69 feet to a set 1/2 inch iron rod with a "GAI" cap, for the beginning of a tangent curve to the left having a radius of 540.00 feet, a central angle of 18°18'05", and a long chord which bears South 47°39'23" West, 171.75 feet;

THENCE along said tangent curve to the left, an arc length of 172.49 feet to a set 1/2 inch iron rod with a "GAI" cap:

THENCE South 38°30'20" West, a distance of 793.55 feet to a set 1/2 inch iron rod with a "GAI" cap;

THENCE South 08°32'44" East, a distance of 13.63 feet to a set 1/2 inch iron rod with a "GAI" cap, being in said east right-of-way line of U.S. Highway No. 287 and said west line of said 2021 South Pointe Holdings LTD. tract, being a common line;

THENCE North 55°35'47" West, along said common line, a distance of 1663.11 feet to a TxDOT Monument (Broken), for the beginning of a tangent curve to the right having a radius of 2,724.79 feet, a central angle of 22°31'40", and a long chord which bears North 44°21'14" West, 1064.45 feet;

THENCE along said tangent curve to the right, and continuing along said common line, an arc length of 1071.34 feet to a TxDOT Monument (Broken):

THENCE North 33°04'03" West, a distance of 444.13 feet to a TxDOT Monument (Broken), for the beginning of a tangent curve to the left having a radius of 1,285.92 feet, a central angle of 2°50'47", and a long chord which bears North 34°30'51" West, 63.88 feet;

THENCE along said tangent curve to the left, an arc length of 63.88 feet to the POINT OF BEGINNING and CONTAINING 2,561,371 square feet, 58.801 acres of land, more or less.

SURVEYOR'S CERTIFICATE

This is to certify that I, MICHAEL L. PETERSON, a Registered Professional Land Surveyor of the State of Texas, having platted the above subdivision from an actual survey on the ground, and that all lot corners, and angle points, and points of curve shall be properly marked on the ground, and that this plat correctly represents that survey made by me or under my direction and supervision.

MICHAEL L. PETERSON Texas Registration No. 5999



STATE OF TEXAS: COUNTY OF TARRANT:

BEFORE ME, the undersigned authority, a Notary Public in and for the State of Texas, on this day personally appeared MICHAEL L. PETERSON, known to me to be the person whose name is subscribed to the foregoing instrument and acknowledge to me that he executed the same in and for the purpose and consideration

GIVEN UNDER MY HAND AND SEAL OF OFFICE this _____ day of _____, 20___

Notary Public in and for the State of Texas

My commission expires ______

LOTS 2-7, BLOCK 1: LOTS 1-4, BLOCK 2: LOTS 1-10,

BLOCK 3: LOTS 41, 42, 44-47, BLOCK 6: LOTS 1-6, 13-15

BLOCK 11: LOTS 6-8. BLOCK 12: AND LOTS 8-12.

BLOCK 13 ARE LOCATED WITHIN 300 FEET OF AN

APPROVED GAS WELL DRILL SITE.

CONDITIONS OF ACCEPTANCE OF DRAINAGE AND FLOODWAY EASEMENTS

THIS PLAT IS PROPOSED BY THE OWNERS OF PROPERTIES DESCRIBED HEREIN (HEREINAFTER REFERRED TO AS "PROPERTY OWNERS) AND IS APPROVED BY THE CITY OF MANSFIELD SUBJECT TO THE FOLLOWING CONDITIONS WHICH SHALL BE BINDING UPON THE PROPERTY OWNERS. HIS HEIRS, GRANTEES. SUCCESSORS AND ASSIGNS.

NO OBSTRUCTION TO THE FLOW OF STORMWATER RUN-OFF SHALL BE PERMITTED BY FILLING OR BY CONSTRUCTION OF ANY TYPE OF DAM, BUILDING, BRIDGE, FENCE, OR ANY OTHER STRUCTURE WITHIN THE DRAINAGE EASEMENT SHOWN HEREIN ON THIS PLAT, UNLESS APPROVED BY THE CITY OF MANSFIELD. PROVIDED. HOWEVER. IT IS UNDERSTOOD THAT IN THE EVENT IT BECOMES NECESSARY FOR THE CITY OF MANSFIELD TO ERECT DRAINAGE FACILITIES IN ORDER TO IMPROVE THE STORM DRAINAGE THAT MAY BE OCCASIONED BY THE STREETS AND ALLEYS IN OR ADJACENT TO THE SUBDIVISION. THEN IN SUCH EVENT, THE CITY OF MANSFIELD SHALL HAVE THE RIGHT TO ENTER SAID DRAINAGE EASEMENT AT ANY POINT OR POINTS TO ERECT, CONSTRUCT AND MAINTAIN ANY FACILITY DEEMED NECESSARY FOR DRAINAGE PURPOSES.

THE PROPERTY OWNERS WILL BE RESPONSIBLE FOR MAINTAINING SAID DRAINAGE EASEMENT. THE PROPERTY OWNERS SHALL KEEP SAID DRAINAGE EASEMENT CLEAN AND FREE OF DEBRIS, SILT, HIGH WEEDS, AND ANY SUBSTANCE WHICH WOULD RESULT IN UNSANITARY OR UNDESIRABLE CONDITIONS. THE CITY OF MANSFIELD SHALL HAVE THE RIGHT OF INGRESS AND EGRESS FOR THE PURPOSE OF INSPECTING AND SUPERVISING MAINTENANCE WORK DONE BY THE PROPERTY OWNERS. IF AT ANY TIME THE PROPERTY OWNERS FAIL TO SATISFY ANY OF THEIR AFOREMENTIONED RESPONSIBILITIES OR OBLIGATIONS, THE CITY OF MANSFIELD, UPON TEN (10) DAYS PRIOR NOTICE TO THE OWNERS, MAY ENTER SAID DRAINAGE FASEMENT AT ANY POINT OR POINTS TO PERFORM MAINTENANCE OR CLEAN-UP, AND BILL THE PROPERTY OWNERS THE COST INCURRED, OR PLACE A LIEN ON SAID PROPERTIES IF THE BILL IS NOT PAID WITHIN THIRTY (30) DAYS OF ITS MAILING.

SAID DRAINAGE EASEMENT. AS IN THE CASE OF ALL DRAINAGE EASEMENTS, IS SUBJECT TO STORMWATER OVERFLOW AND EROSION TO AN EXTENT WHICH CANNOT BE SPECIFICALLY DEFINED. THE CITY OF MANSFIELD SHALL NOT BE HELD LIABLE FOR ANY DAMAGES RESULTING FROM THE OCCURRENCE OF THESE NATURAL PHENOMENA OR THE FAILURE OF ANY FACILITIES WITHIN SAID DRAINAGE EASEMENT. FURTHER, THE CITY OF MANSFIELD WILL NOT BE RESPONSIBLE FOR EROSION CONTROL OR ANY DAMAGE TO PRIVATE PROPERTIES OR PERSONS RESULTING FROM THE FLOW OF WATER WITHIN SAID DRAINAGE EASEMENT AND PROPERTIES.

IND TROI	NO TROI EIRIES.							
Parcel Line Table								
LINE #	LENGTH DIRECTION							
L1	54.06	N81° 46′ 12"W						
L2	41.47'	N5° 46' 08"E						
L3	9.40'	N35° 58' 47"W						
L4	13.02'	S89° 24' 13"E						
L5	11.57'	S16° 14' 57"W						
L6	10.39'	N17° 25' 34"W						
L7	13.57'	N88° 28' 45"E						
L8	14.14'	S85° 52' 44"W						
L9	14.14'	S6° 29′ 40″E						
L10	60.01	S40° 48′ 35"W						
L11	13.74'	S6° 00' 14"E						
L12	60.00'	S49° 07' 16"E						
L13	14.14'	S83° 30' 20"W						
L14	87.69'	S56° 48' 25"W						
L15	198.56'	S38° 30' 20"W						
L17	25.00'	N36° 37' 26"E						
L17	25.00'	N36° 37' 26"E						

	CURVE TABLE							
CURVE #	Δ	RADIUS	TANGENT	LENGTH	LCB	LCD		
C-1	83° 31′ 29″	42.50'	37.95'	61.96'	S82° 38′ 29"W	56.61		
C-2	22° 31′ 44″	2545.00'	506.90'	1000.70	N44° 19' 55"W	994.26		
C-3	40° 34′ 30″	225.00'	83.17'	159.34	N12° 46′ 48″W	156.03		
C-4	46° 10' 12"	42.50'	18.11'	34.25'	N75° 08' 42"E	33.33'		
C-5	11° 14' 41"	300.00'	29.53'	58.88'	S76° 08' 51"E	58.78		
C-6	99° 30′ 00″	42.50'	50.20'	73.81'	S20° 46′ 31″E	64.87		
C-7	12° 14′ 46″	250.00'	26.82'	53.43'	S35° 05' 52"W	53.33'		
C-8	30° 08' 54"	100.00'	26.93'	52.62'	N66° 41' 45"W	52.01		
C-9	18° 18' 05"	630.00'	101.48	201.23	S47° 39' 23"W	200.38		
C-10	49° 21' 07"	100.00'	45.94'	86.14	S73° 33' 15"W	83.50'		
C-11	10° 25' 46"	1120.00	102.22	203.87	N36° 00' 23"E	203.59		
C-12	25° 01' 22"	580.00'	128.70'	253.30'	N18° 16' 49"E	251.29		
C-13	5° 20' 31"	550.00'	25.66'	51.28'	N52° 55' 03"W	51.26		
C-14	2° 47' 22"	520.00'	12.66'	25.32'	S55° 24' 44"W	25.31		
C-15	3° 10' 44"	2259.79	62.71'	125.38'	N54° 00' 25"W	125.36		
C-16	2° 10′ 36″	575.00'	10.92'	21.85'	N55° 43' 07"E	21.84		
C-17	85° 53′ 52″	42.50'	39.56'	63.72'	N81° 27' 16"E	57.91		
C-18	5° 40' 13"	1030.00	51.01'	101.94	N35° 40' 14"E	101.89		
C-19	56° 34' 14"	42.50'	22.87'	41.96'	N4° 33' 00"E	40.28		
C-20	16° 15' 17"	300.00'	42.84'	85.11'	N31° 51' 45"W	84.82		
C-21	4° 00' 37"	2295.00'	80.35'	160.63	N37° 59' 05"W	160.60		
C-22	13° 39' 44"	300.00'	35.94'	71.53'	N42° 48′ 39"W	71.37		
C-23	75° 49' 01"	42.50'	33.10'	56.24'	N87° 33' 02"W	52.22		
C-24	13° 39' 44"	300.00'	35.94'	71.53'	S47° 42′ 36″W	71.37		
C-25	96° 28′ 31″	42.50'	47.60'	71.56'	S7° 21' 32"E	63.40'		
C-26	5° 40' 13"	750.00'	37.14'	74.22'	N35° 40' 14"E	74.19		
C-27	10° 14' 24"	750.00'	67.20'	134.04	N37° 57' 19"E	133.86		
C-28	6° 27' 04"	750.00'	42.27'	84.45'	N39° 50' 59"E	84.40'		
C-29	14° 53′ 18″	500.00'	65.33'	129.92'	N44° 04' 05"E	129.56		
C-30	0° 26′ 20″	2040.00'	7.81'	15.63'	S39° 46′ 14″E	15.63'		
C-31	18° 18' 05"	575.00'	92.62'	183.67	N47° 39' 23"E	182.89		
C-32	5° 40' 13"	890.00'	44.08'	88.08'	S35° 40' 14"W	88.04		
C-33	5° 29' 09"	610.00'	29.22'	58.40'	S35° 34' 42"W	58.38		
C-34	21° 22′ 13″	1310.93	247.35	488.95	N43° 39′ 47"W	486.12		

PRELIMINARY PLAT SOUTHPOINTE PHASE 7A & 7B

58.801 ACRES OUT OF THE SETH M. BLAIR SURVEY ABSTRACT NO. 72 AND CRESANTO VELA SURVEY ABSTRACT NO. 851 AS RECORDED IN DOC. NO. 2022-58, P.R.J.C.T. CITY OF MANSFIELD, JOHNSON COUNTY, TEXAS

> 180 RESIDENTIAL LOTS 7 OPEN SPACE LOTS

> > May 2023

PREPARED BY

Graham Associates, Inc. **CONSULTING ENGINEERS & PLANNERS** 600 SIX FLAGS DRIVE, SUITE 500 ARLINGTON, TEXAS 76011 (817) 640-8535

ENGINEER: DFWTX DEVELOPMENT. INC. GRAHAM ASSOCIATES, INC. 7676 WOODWAY, SUITE 104 CONSULTING ENGINEERS & PLANNERS HOUSTON, TX 77063 600 SIX FLAGS DRIVE, SUITE 500 ARLINGTON, TEXAS 76011 TEL: (713) 952-6767 CONTACT: GARY R TESCH. PRESIDENT TEL:(817) 640-8535 EMAIL: GTESCH@MHINC.COM





AFTER RECORDING, RETURN TO THE CITY OF MANSFIELD 1200 E. BROAD STREET, MANSFIELD, TEXAS 76063

FAX:(817) 633-5240 INFORMATION@GRAHAMCIVIL.COM

SD#23-013

SHEET 6 OF