

THE CITY OF MANSFIELD

STANDARD CONSTRUCTION DETAILS



ENGINEERING DEPT.
APRIL 2021


THE STANDARD SPECIFICATIONS FOR CONSTRUCTION SHALL BE THE 5TH EDITION OF THE "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION" PREPARED BY THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS EXCEPT AS AMENDED BY THESE STANDARD DETAILS & C.O.M. MATERIAL TESTING POLICIES.

SHEET INDEX

SHEET No.	DESCRIPTION
P-1	PAVING - TYPICAL STREET SECTIONS: ARTERIALS
P-2	PAVING - MEDIAN, LEFT TURN LANE, & CONDUIT DETAILS
P-3	PAVING - TYPICAL STREET SECTIONS: RESIDENTIAL & COLLECTORS
P-4	PAVING - DRIVE APPROACHES, CURB, & ASPHALT DETAILS
P-5	PAVING - JOINT & SEALANT DETAILS
P-6	PAVING - SIDEWALK & RAMP DETAILS
P-7	PAVING - BARRICADE & SUBDRAIN DETAILS
P-8	PAVING - STRIPING, PAVEMENT MARKERS, SIGNS
SD-1	STORM DRAIN - CURB INLET DETAILS
SD-2	STORM DRAIN - MANHOLE AND DROP INLET DETAILS
SD-3	STORM DRAIN - TRENCH, COLLAR & MISCELLANEOUS DETAILS
SD-4	STORM DRAIN - TYPE "A" AND "B" HEADWALLS
SD-5	STORM DRAIN - TYPE "P" HEADWALLS
W-1	WATER - WATER SERVICE, GENERAL NOTES & TRENCH DETAILS
W-2	WATER - GATE VALVE, BLOCKING, MARKER & LOWERING DETAILS
W-3	WATER - BLOW OFF & AIR RELEASE VALVE DETAILS
W-4	WATER - FIRE HYDRANT, TEMPORARY FLUSH VALVE, & BORE DETAILS
W-5	WATER- 3" & LARGER WATER SERVICE DETAILS
W-6	WATER- 3" & LARGER BACKFLOW PREVENTION DEVICE DETAILS
SS-1	SANITARY SEWER - MANHOLE & CLEANOUT DETAILS
SS-2	SANITARY SEWER - SERVICE & TRENCH DETAILS
M-1	MISCELLANEOUS- TRENCH DETAILS
MS-1	MATERIAL SPECIFICATIONS
MS-2	MATERIAL SPECIFICATIONS

GENERAL NOTES:


- 1. ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION, UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
- 2. SEE SHEET P-3 FOR PAVING GENERAL NOTES.
- 3. SEE OTHER PAVING DETAIL SHEETS FOR WALKWAY, CURB, JOINTING, STRIPING AND OTHER RELATED CONSTRUCTION DETAILS.
- 4. ALL CURBS MUST BE MONOLITHIC.



STANDARD SECTION
N.T.S.


- (A) 9" CONCRETE PAVEMENT WITH MONOLITHIC CURB WITH #4 STEEL REINFORCING BARS ON 18" CENTERS BOTH WAYS IN CENTER OF SLAB.
- (B) 12" STABILIZED SUBGRADE (SEE SHEET P-3, NOTE 5).
- (C) FILL EMBANKMENTS (EXTENDING TO EDGE OF SLOPES) SHALL BE COMPACTED TO A MINIMUM 95% ASTM D698 IN MAXIMUM 12" LOOSE, 6" COMPACTED LAYERS. MOISTURE SHALL BE OPTIMUM AND ABOVE.

NOTE:
PROVIDE EROSION CONTROL
BLANKET ON SLOPES GREATER
THAN 4:1.




STANDARD SECTION
N.T.S.

NOTE:
PROVIDE EROSION CONTROL
BLANKET ON SLOPES GREATER
THAN 4:1.



LEFT TURN SECTION
N.T.S.




LEFT TURN SECTION
N.T.S.

6 – LANE DIVIDED PRINCIPLE ARTERIAL (P6D) TYPICAL SECTIONS

4 – LANE DIVIDED MAJOR ARTERIAL (M4D) TYPICAL SECTIONS

TYPICAL STREET SECTIONS: ARTERIALS		
CITY OF MANSFIELD STANDARD CONSTRUCTION DETAILS		
PAVING	DATE: APR. 2021	SHEET NO. P-1




TYPICAL CROSS SECTION

N.T.S.

NOTE: EXPANSION JOINTS IN PAVING TO BE EXTENDED THROUGH PAVER SECTIONS.

MEDIAN PAVING STONE DETAIL


N.T.S.



CONDUIT

N.T.S.

INTERSECTION CROSSING:
2-4" SCH. 40 PVC CONDUITS (PER CROSSING)




SECTION

CONCRETE MEDIAN CAP

N.T.S.

GENERAL NOTES:

1. ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS, OR MATERIAL TESTING POLICIES.
2. PVC CONDUIT TO BE INSTALLED CONTINUOUS ACROSS INTERSECTION, EXTENDING TO 5' BEHIND CURBS OR PAVE STONES, TERMINATING IN PULL BOX W/LONG SWEEP 90° BENDS & CAPPED (BOX-DFW D-1500, OLSB).
3. RED MARKER TAPE IS TO BE INSTALLED ON THE ENDS OF THE CONDUIT.
4. THE EXACT LOCATIONS WHERE THE CONDUIT CROSSES UNDER THE PAVEMENT IS TO BE MARKED WITH RED PAINT ON THE CURB OR PAVING. A NYLON CORD SHALL BE PLACED IN ALL CONDUIT. THE CORD SHALL EXTEND A MINIMUM 1' FROM THE END OF THE CONDUIT.
5. ALL CONDUIT SHALL BE PLACED ADJACENT TO THE CURB WITH A BURY DEPTH OF 3'-0" BELOW FINISHED GRADE AND BE SPACED ONE FOOT APART.
6. SCH. 40 CONDUIT PLACEMENT SHALL BE WEST OF CENTER LINE OF ELECTRICAL CONDUIT ON STREETS RUNNING NORTH & SOUTH & NORTH OF CENTERLINE OF ELECTRIC CONDUIT ELECTRIC ON STREETS RUNNING EAST & WEST. SCH. 80 CONDUIT (ELECTRIC) TO BE PLACED AT CENTERLINE OF R.O.W.
7. CONDUIT BACK FILL TO BE NATIVE MATERIAL MECHANICALLY TAMPED TO 95% OF ASTM D698, OPTIMUM MOISTURE OR ABOVE PER NCTCOG ITEM 504.
8. FOR TURN LANES ADDED TO EXISTING STREETS, CEMENT TREATED SAND MAY BE USED FOR LIME SUBSTITUTE SUB-GRADE AT DISCRETION OF CITY ENGINEER.



LEFT TURN LANE LAYOUT DETAIL

N.T.S.

1. ALL DIMENSIONS ARE TO BACK OF CURB UNLESS NOTED OTHERWISE.
2. TURN LANES TO BE 11'-0" TO FACE OF CURB, MAIN LANES 12'-0".
3. MEDIAN NOSES TO BE SEMI-CIRCLES, EXCEPT WHERE 4 LANES INTERSECT 4 LANES OR LARGER.
4. TURN LANES AND MEDIAN OPENINGS TO BE DETERMINED BY ROADWAY AND ACCESS MANAGEMENT DESIGN CRITERIA.

MEDIAN, LEFT TURN LANE, &
CONDUIT DETAILS

CITY OF MANSFIELD
ENGINEERING DEPARTMENT


PAVING

DATE:
APR. 2021

SHEET NO.
P-2


GENERAL NOTES:

1. ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
2. CONCRETE FOR MACHINE PAVING TO BE CLASS P1 (5½ SACK, 4000 PSI) AND CONCRETE FOR HAND PAVING TO BE CLASS P2 (6 SACK, 4500 PSI) PER NCTCOG SPEC. 303.3.4.2. ALL CONCRETE SHALL CONTAIN SUFFICIENT AIR ENTRAINING AGENT TO YIELD 5% AIR CONTENT. ALL OTHER ADMIXTURES SHALL REQUIRE THE PERMISSION OF THE ENGINEERING DEPARTMENT. ALL MIX DESIGNS TO BE 100% CRUSHED ANGULAR STONE WITH A MAXIMUM SIZE OF 1". FLY ASH MAY BE USED IN MIX DESIGNS AS DETAILED IN NCTCOG, ITEM 303.2.4, 20% MAX. FINE AGGREGATE NOT TO EXCEED 25% MANUFACTURED SAND. BATCH PLANTS REQUIRE SPECIAL USE PERMIT.
3. AN APPROVED WHITE PIGMENTED CURING COMPOUND SHALL BE APPLIED TO THE SURFACE OF THE PAVEMENT AS SOON AS IT HAS BEEN PLACED AND FINISHED.
4. CONCRETE STREET PAVEMENT SHALL BE CONSTRUCTED BY USE OF A PAVING MACHINE THAT INCORPORATES AN AUGER/STRIKE OFF UNIT, HYDRAULICALLY POWERED, MOTOR-IN-HEAD, VARIABLE SPEED, INDEPENDENTLY CONTROLLED VIBRATORS (MIN. 4 VIBRATORS 2" DIAMETER HEADS MIN., SPACE 2' APART MAX.) AND AN INTEGRATED MONOLITHIC VIBRATED "CURB MULE". HAND PLACEMENT OF STREET PAVEMENT WILL ONLY BE ALLOWED FOR AREAS NOT POSSIBLE WITH A MACHINE (EX. CUL-DE-SACS, INTERSECTIONS, EYEBROWS, SMALL BLOCK-OUTS, ETC.).
5. CITY OF MANSFIELD SHALL REVIEW LIME SERIES RECOMMENDATION FROM GEOTECHNICAL ENGINEER TO DETERMINE PERCENTAGE OF LIME OR PORTLAND CEMENT NECESSARY TO PREPARE SUBGRADE. 6% (36 LBS./S.Y. FOR 8" OR 54 LBS./S.Y. FOR 12") WILL BE MINIMUM LIME OR CEMENT CONTENT. SEE C.O.M. MATERIAL TESTING POLICIES FOR ADDITIONAL INFORMATION.
6. ALL REINFORCING STEEL SHALL BE DEFORMED BARS CONFORMING TO ASTM A-615 GRADE 60. REINFORCING STEEL SHALL BE PLACED WITH A MINIMUM OF 1½" OF COVER FOR #5 BARS OR SMALLER. WHERE REINFORCING BARS ARE SPLICED, A 30 DIAMETER LAP SHALL BE USED.
7. SEE JOINT DETAIL SHEET P-5 FOR JOINT DETAILS, SPACING, JOINT MATERIALS, AND SEALANT.
8. THE CONTRACTOR SHALL INSTALL SUPPORTING CHAIRS, WITH PLATES OR BASES, FOR REINFORCING STEEL ON A ONE SQUARE YARD SPACING IN ALL CONCRETE PAVEMENT.
9. PAVEMENT TO INSTALL GRIPPER PLUGS IN PIPE ENDS OF ALL MANHOLES OR FALSE BOTTOMS IN "IN SERVICE" MANHOLES PRIOR TO EXCAVATION OR SUBGRADE PREPARATION. MANHOLES SHALL BE PLACED MONOLITHIC WITH STREET.
10. MAJOR COLLECTORS AND ALL 4 LANE ARTERIALS OR LARGER SHALL HAVE SUBDRAINS INSTALLED AT BACK OF CURB ON BOTH SIDES OF ROAD WHERE GROUND WATER OR IRRIGATION WATER IS ANTICIPATED TO BE PRESENT. CITY ENGINEER SHALL DETERMINE LOCATIONS (SEE SHEET P-7).
11. ALL STREETS SHALL RECEIVE MEDIUM BAKER BROOM FINISH.
12. MAINTAIN 2% MAXIMUM CROSS SLOPE FOR FULL WIDTH OF PEDESTRIAN ROUTES AND CROSSWALKS THAT CROSS DRIVEWAYS AND INTERSECTIONS. SEE SHEETS P-6 & P-8 FOR ADDITIONAL ACCESSIBILITY REQUIREMENTS.
13. MATERIALS USED AS TOPSOIL MUST BE PRE-APPROVED BY ENGINEER.




NOTE:
PROVIDE EROSION CONTROL
BLANKET ON SLOPES GREATER
THAN 4:1.

LOCAL RESIDENTIAL (RES2U)
N.T.S.



NOTE:
PROVIDE EROSION CONTROL
BLANKET ON SLOPES GREATER
THAN 4:1.

LOCAL COLLECTOR (RESIDENTIAL, C2U, 37')
N.T.S.
MINOR COLLECTOR (C3U, 39')
N.T.S.




NOTE:
PROVIDE EROSION CONTROL
BLANKET ON SLOPES GREATER
THAN 4:1.


MAJOR COLLECTOR (C4U)
N.T.S.

TYPICAL STREET SECTIONS:
RESIDENTIAL AND COLLECTORS
CITY OF MANSFIELD
STANDARD CONSTRUCTION DETAILS

PAVING	DATE: APR. 2021	SHEET NO. P-3
--------	--------------------	------------------



PLAN VIEW




SECTION A-A

NOTES:


- EXISTING CURB AND GUTTER, IF ANY, MUST BE SAWED.
- REINFORCE DRIVE WITH #3 BARS AT 18" CENTERS, BOTH WAYS, SUPPORTED BY STANDARD CHAIRS (3' MAX. SPACING).
- SIDEWALK SECTION THRU DRIVEWAY TO BE THE SAME THICKNESS AS THE DRIVEWAY APPROACH & TOOLED TO MATCH SIDEWALK.
- SCARIFY, REMOVE ORGANIC MATERIALS, AND COMPACT SUBGRADE TO MINIMUM 95% ASTM D698, OPTIMUM MOISTURE CONTENT OR ABOVE.
- DRILL INTO EXISTING STREET AT 18" CENTERS PER DETAIL SHT. P-5, BUTT JOINT DETAIL.
- DRIVEWAY CURB CUT SHALL NOT EXTEND INTO INTERSECTION RADIUS OR CURB INLET TRANSITION.
- DRIVEWAY REQUIRING CULVERTS: CULVERT MUST BE MIN. 18" AND BE RCP OR HDPE W/ TYPE P HEADWALL.
- DRIVE APPROACH W/ 3-CAR GARAGE FACING STREET: 24' WIDTH MAX. MAY BE USED PER PLAN. ALL OTHERS MUST BE MAXIMUM 20'.

RESIDENTIAL DRIVE APPROACH

N.T.S.



PLAN VIEW



SECTION B-B

NOTES:


- EXISTING CURB AND GUTTER, IF ANY, MUST BE SAWED.
- REINFORCE DRIVE WITH #4 BARS AT 12" CENTERS, BOTH WAYS, SUPPORTED BY STANDARD CHAIRS (3' MAX. SPACING).
- SIDEWALK SECTION THRU DRIVEWAY TO BE THE SAME THICKNESS AS THE DRIVEWAY APPROACH & TOOLED TO MATCH SIDEWALK.
- SCARIFY, REMOVE ORGANIC MATERIALS, AND COMPACT SUBGRADE TO MINIMUM 95% ASTM D698, OPTIMUM MOISTURE CONTENT OR ABOVE.
- DRILL INTO EXISTING STREET AT 12" CENTERS PER DETAIL SHT. P-5, BUTT JOINT DETAIL.
- DRIVEWAY CURB CUT SHALL NOT EXTEND INTO INTERSECTION RADIUS OR CURB INLET TRANSITION.

COMMERCIAL DRIVE APPROACH

N.T.S.


GENERAL NOTES:

- ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
- ALL CONCRETE SHALL MEET THE QUALITY ON GENERAL PAVING STANDARDS SHEET.
- DRIVE APPROACH BLOCK OUTS TO BE 2'6" FROM BACK OF CURB INTO SLAB AND EXTEND FROM CURB RETURN TO CURB RETURN.
- ALL CONCRETE SHALL BE CLASS "C" CONTAINING A MINIMUM OF 6 SACKS OF TYPE 1 CEMENT PER YARD AND HAVE A MINIMUM COMPRESSIVE STRENGTH OF 3,600 P.S.I. AT 28 DAYS (303.3.4.2). AGGREGATE SHALL BE 100% CRUSHED ANGULAR STONE (1" MAX.). ALL CONCRETE PLACED SHALL CONTAIN SUFFICIENT AIR ENTRAINING AGENT TO YIELD 5% AIR CONTENT. ALL OTHER ADMIXTURES SHALL REQUIRE THE PERMISSION OF THE ENGINEERING DEPARTMENT. FLY ASH MAY BE USED IN MIX DESIGNS AS DETAILED IN NCTOG ITEM 303.2.4., 20% MAX. FINE AGGREGATE NOT TO EXCEED 25% MANUFACTURED SAND.
- ALL DRIVE APPROACHES AND SIDEWALKS SHALL RECEIVE A LIGHT BROOM FINISH.



TYPICAL SECTION - MONOLITHIC CURB

N.T.S.



NOTE:

BASE-8" CRUSHED STONE BASE COMPACTED TO A MINIMUM OF 95% OF STANDARD PROCTOR AT OPTIMUM MOISTURE OR 8" LIME STABILIZED MATERIAL (TEX 113E).


ASPHALT-4" BINDER BASE 2" TYPE "D" SURFACE (CRUSHED STONE TYPE) (TXDOT 341)

TACK COAT - 0.05 GAL/S.Y. OF MC - 30 TO BE APPLIED IF SURFACE OF HMAc IS OPENED TO TRAFFIC OR ALLOWED TO SET BETWEEN PLACEMENTS.


TEMPORARY ASPHALT TRANSITION DETAIL

N.T.S.


DRIVE APPROACHES, CURB, & ASPHALT DETAILS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
PAVING	DATE: APR. 2021	SHEET NO. P-4




CONSTRUCTION JOINT
N.T.S.



SAWED CONTRACTION JOINT
N.T.S.




BUTT JOINT
N.T.S.



NOTE:

1. CAPPED SIDE OF DOWEL TO BE GREASED.
2. 3/4" JOINT TO BE USED IN PAVEMENT, 1/2" JOINT TO BE USED IN SIDEWALK.


EXPANSION JOINT
N.T.S.



NOTES:

1. E-DENOTED EXPANSION.
2. REFER TO SECTION FOR LONGITUDINAL JOINT LOCATIONS.
3. SAWED TRANSVERSE OR CONSTRUCTION JOINTS SPACED 15'-0".
4. PLACE EXPANSION JOINTS AT INTERSECTIONS, BEGINNING AND ENDING OF HORIZONTAL CURVES, AND AT MAXIMUM 500' SPACING ALONG ROADWAY.
5. ON CONCRETE STREETS, ALL INLETS SHALL BE SEPARATED FROM THE PAVEMENT AND CURB BY BLOCKING OUT AS SHOWN ON SHEET SD-1.
6. EXTEND EXPANSION JOINT THROUGH PAVER SECTIONS ON DIVIDED ROADWAY (P-2).

SPACING DIAGRAM FOR TRANSVERSE JOINTS
N.T.S.



NOTE:


PAVEMENT BARS TO BE BENT DOWN INTO HEADER AND PAVEMENT TO BE MONOLITHIC.

CONCRETE HEADER
N.T.S.


GENERAL NOTES:

T= PAVEMENT THICKNESS

1. ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
2. CONTRACTOR MUST USE MONOLITHIC CURB UNLESS DOWELED CURB IS PRE-APPROVED BY ENGINEERING DEPARTMENT.
3. DOWEL BARS OR REBAR PLACED INTO EXISTING PAVEMENT SHALL BE DRILLED INTO PAVEMENT HORIZONTALLY. PUSHING DOWEL BARS OR REBAR INTO GREEN CONCRETE IS NOT ACCEPTABLE. SECURE DOWEL BARS OR REBAR INTO EXISTING PAVING WITH EPOXY GROUT INJECTED INTO HOLE WITH CAULKING GUN.
4. SEALANT SHALL BE SELF-LEVELING SILICONE PER CITY OF MANSFIELD DETAIL: "SILICONE JOINT SEALANT FOR CONCRETE PAVEMENT."
5. THE CONSTRUCTION JOINT IS TO BE USED BETWEEN SEPARATE POURS OF PROPOSED PAVEMENT. NOTE THAT IT REQUIRES THE REINFORCEMENT TO BE EXTENDED THROUGH THE FORM TO TIE TO THE NEXT POUR. THE BUTT JOINT IS TO BE USED BETWEEN EXISTING CONCRETE PAVEMENT (STREET, DRIVEWAY, OR BLOCK OUT) AND PROPOSED PAVEMENT, UNLESS AN EXPANSION JOINT IS CALLED FOR OR AN "L" BAR IN A KEYWAY MAY BE ATTACHED TO STEEL MAT TO BE BENT OUT INTO NEXT PLACEMENT. TWO-PIECE TIE BARS MAY ALSO BE USED. DRILL AND EPOXY WILL ONLY BE PERMITTED ON EXISTING PAVEMENT.




SEALANT DETAIL FOR TRANSVERSE EXPANSION JOINT
N.T.S.



SEALANT DETAIL FOR SAWED CONTRACTION JOINT
N.T.S.


JOINT & SEALANT DETAILS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
PAVING	DATE: APR. 2021	SHEET NO. P-5



STANDARD SIDEWALK SECTION


N.T.S.

SIDEWALK JOINTS SHALL BE GROOVED 3/8" DEEP W/ REDWOOD EXPANSION JOINTS EVERY 40' MAX. W/24"- #4 SMOOTH DOWELS @ 12" CENTERS




STANDARD SIDEWALK PLAN

N.T.S.



PERPENDICULAR RAMP


N.T.S.



INTERSECTION RAMP


N.T.S.

NOTE: CURB LAYDOWN AND OPENING TO BE 1' WIDER THAN LARGEST INTERSECTION WALK.




DIRECTIONAL CURB RAMP

N.T.S.




SIDEWALK ABUTTING CURB SECTION

N.T.S.




PARALLEL RAMP

N.T.S.



SIDEWALK WITH CURB AND TOEWALL


N.T.S.



SIDEWALK WITH RETAINING WALL


N.T.S.

- NOTES:
1. INSTALL 1" DIA. PVC WEEP HOLE ON 10' CENTERS.
 2. SIDEWALK JOINTING TO BE CONTINUOUS UP FACE OF WALL WITH CHAMFER.



DIRECTIONAL CURB RAMP FOR WALK ABUTTING CURB

N.T.S.



SPLIT RAMPS (STREET RADIUS < 15')

N.T.S.

SIDEWALK GENERAL NOTES:

1. ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
2. CONCRETE SHALL BE A MINIMUM OF 4 INCHES THICK, CLASS "A", (303.3.4.2) CONTAINING A MINIMUM OF 5 SACKS OF TYPE 1 CEMENT PER YARD (3000 PSI). AGGREGATE SHALL BE 100% CRUSHED ANGULAR STONE (1" MAX.). ALL CONCRETE PLACED SHALL CONTAIN SUFFICIENT AIR ENTRAINING AGENT TO YIELD 5% AIR CONTENT. FINE AGGREGATE NOT TO EXCEED 50% MANUFACTURED SAND.
3. CHAMFER ALL EXPOSED EDGES OF CONCRETE WALLS 3/4 INCH.
4. ALL REINFORCING STEEL SHALL BE DEFORMED BARS CONFORMING TO ASTM A-615 GRADE 60. REINFORCING STEEL SHALL BE PLACED WITH A MINIMUM OF 1-1/2 INCH OF COVER FOR #5 BARS OR SMALLER. WHERE REINFORCING BARS ARE SPLICED, A 30 DIAMETER LAP SHALL BE USED.
5. CURBED RAMP BLOCK OUTS TO BE 1'6" FROM BACK OF CURB INTO SLAB AND EXTEND FROM CURB RETURN TO CURB RETURN.
6. SUBGRADE SHALL CONSIST OF NATIVE SOIL OR SAND COMPACTED TO A DENSITY NOT LESS THAN 95% ASTM D698, OPTIMUM MOISTURE CONTENT OR ABOVE.
7. SIDEWALKS SHALL BE FINISHED BY LIGHTLY BROOMING SURFACE TRANSVERSE TO DIRECTION OF TRAFFIC.
8. AN APPROVED WHITE PIGMENTED CURING COMPOUND SHALL BE APPLIED TO THE SURFACE OF THE PAVEMENT AS SOON AS IT HAS BEEN PLACED AND FINISHED.
9. RETAINING WALLS TO HAVE REDWOOD EXPANSION JOINTS @ 40' MAX. W/24"- #4 SMOOTH DOWELS @ 12" CENTERS. SIDEWALK JOINTS TO BE CHAMFERED THROUGH WALL (3/4" TYP.).
10. FOR ADDITIONAL INFORMATION AND DETAILS, SEE TXDOT PED STANDARDS, US ACCESS BOARD PROWAG, AND TAS REGULATIONS.
11. TRUNCATED DOMES TO BE APPROVED ANTIQUE RED BLOCK PAVERS ONLY.
12. ALL JOINTS IN PAVEMENT TO BE SEALED (P-5).

SIDEWALK & RAMP
DETAILS

CITY OF MANSFIELD
STANDARD CONSTRUCTION DETAILS


PAVING

DATE:
APR. 2021

SHEET NO.
P-6


TEMPORARY END OF ROAD BARRICADE DETAILS

1. ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED ABOVE SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION, UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
2. ALL INSTALLATION SHALL BE OF NEW MATERIALS. METAL FLEX-BEAM GUARDRAIL SHALL BE 10 GAUGE, GALVANIZED AS PER ASTM A 93. SUBSTITUTIONS OF ANY ITEM SHALL BE APPROVED BY THE ENGINEERING DEPARTMENT PRIOR TO INSTALLATION.
3. ALL POSTS SHALL BE WOLMANIZED TREATED FOR GROUND CONTACT. SQUARE 6"x6" POSTS (ALSO TREATED) MAY BE SUBSTITUTED, PROVIDED THE TOP OF EACH POST IS BEVELED A MINIMUM OF 10° (DEGREES).
4. ALL BOLTS, WASHERS, OR HARDWARE SHALL BE GALVANIZED TREATED TO RESIST RUST. BOLTS SHALL BE OF SUFFICIENT LENGTH TO EXTEND THROUGH THE THICKNESS OF THE NUT.
5. POSTS SHALL NOT BE CONCRETED IN PLACE, BUT SHALL INSTEAD BE BACK FILLED WITH WELL-TAMPED SOIL.
6. STRIPING-BARRICADES SHOULD HAVE STRIPE SLOPE DOWNWARD IN THE DIRECTION TOWARD WHICH TRAFFIC MUST TURN IN DETOURING. WHEN BOTH RIGHT AND LEFT TURNS ARE PROVIDED FOR, CHEVRONS SHALL SLOPE AWAY FROM CENTER. IF NO TURN IS PROVIDED (END OF ROAD), CHEVRONS SLOPE TOWARD CENTER (AS SHOWN).
7. TYPE III BARRICADES SHALL BE USED BEHIND THE GUARDRAIL BARRICADE AND SHALL MEET MUTCD STANDARDS.




TYPE 3 BARRICADE

N.T.S. (NOTE 7)



ELEVATION


N.T.S.



NOTE: DIAGONAL RED REFLECTIVE TAPE SHALL BE APPLIED ON THE FACE OF ALL GUARD PANELS (THE FULL FACE OF THE PANEL SHALL BE COVERED).


TAPE DETAIL

N.T.S.



METAL BEAM DETAIL

N.T.S.



EACH BARRICADE SHALL CONSIST OF 2 GUARD FENCE PANELS, 2 TERMINAL PIECES AND POSTS - UNLESS OTHERWISE SPECIFIED.


ONE 5/8" BOLT W/LARGE DIA.
WASHER - 7/8" DIA.
HOLE IN POST (MIN.)

POST DETAIL

N.T.S.

SUBDRAIN DETAIL


1. ALL SUBDRAIN PIPES TO BE 6" DIAMETER.
2. FILLER MATERIAL AROUND SUBDRAIN PIPES SHALL BE ¾" CRUSHED STONE, NCTCOG 504.2.2.1 (a) "AGGREGATE GRADE 4".
3. SUBDRAIN PIPE MATERIAL SHALL BE PERFORATED PVC PIPE OR PERFORATED POLYETHYLENE PIPE ENCASED IN "FILTER FABRIC SLEEVE".
4. ALL SUBDRAINS SHALL BE INSTALLED AFTER PAVEMENT AND PRIOR TO SIDEWALK.
5. CLEANOUTS W/CONCRETE PADS (PER SHEET SS-2) SHALL BE PLACED AT 500' INTERVALS ALONG SUBDRAIN AND AT THE UPSTREAM END OF LINE.
6. CONNECTION TO INLET SHALL BE MADE WITH A SECTION OF 6" SCHEDULE 40 PVC PIPE INTO THE INLET SIDE WALL AT TIME OF INLET CONSTRUCTION. THE SUBDRAIN WILL THEN BE ADAPTED TO THE PERFORATED PIPE.



TYPICAL SECTION


N.T.S.

BARRICADE & SUBDRAIN DETAILS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
PAVING	DATE: APR. 2021	SHEET NO. P-7



SINGLE BROKEN LINE

N.T.S.




DOUBLE SOLID LINE

N.T.S.


NOTES:

1. BUTTONS TO BE AS MANUFACTURED BY APEX UNIVERSAL, INC. AND RAY-O-LITE
2. REFLECTORS TO BE AS MANUFACTURED BY RAY-O-LITE.
3. SINGLE BROKEN LINE REFLECTORS TO BE:
 - RSWR WHITE STRIPING (DIVIDED ROADWAY)
 - RS1W WHITE STRIPING (UNDIVIDED ROADWAY)
4. DOUBLE SOLID LINE REFLECTORS TO BE:
 - RS2A FOR YELLOW STRIPING
 - RSWR FOR WHITE STRIPING (DIVIDED ROADWAY)
 - RS1W FOR WHITE STRIPING (UNDIVIDED ROADWAY)



TYPICAL BUTTON LAYOUT FOR 4-LANE ARTERIAL SECTION

N.T.S.




TYPICAL BUTTON LAYOUT FOR 49' B/B STREET SECTION

N.T.S.

NOTE:

1. PAVEMENT PAINTS, MARKINGS, AND TRAFFIC BUTTONS WHERE APPROVED, TO BE IN CONFORMANCE WITH NCTCOG STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION "ITEM 804." PLACEMENT TO BE AS ILLUSTRATED IN CONSTRUCTION PLANS.
2. DO NOT APPLY PAVEMENT MARKINGS UNTIL PAVEMENT SURFACE AND BUTTON LAYOUT HAS BEEN APPROVED BY ENGINEER.
3. ASPHALT ROADWAYS TO BE MARKED WITH THERMO AND WITH RAISED PAVEMENT REFLECTORS PER TXDOT SPECIFICATIONS.



INTERSECTION CROSSWALK

N.T.S.

SIGN SPECIFICATIONS

1. ALL SIGNS SHALL BE STANDARD MUTCD SIGNS ON 0.080" ALUMINUM WITH PRISMATIC GRADE REFLECTIVE SHEETING.
2. ALL SIGN POSTS SHALL BE 1 3/4" (14 GAUGE) SQUARE GALVANIZED POSTS WITH HOLES UTILIZING THE THREE PIECE BREAKAWAY SYSTEM CONSISTING OF THE POSTS LISTED ABOVE, A 2 1/4" X 18" (12 GAUGE) SLEEVE, AND A 2" X 36" (12 GAUGE) ANCHOR.
3. RED SERIES REGULATORY SIGNS SHALL BE 30" X 30".
4. BLACK & WHITE SERIES REGULATORY SIGNS SHALL BE STANDARD MUTCD SIZES EXCEPT FOR SPEED LIMIT AND PARKING SIGNS WHICH SHALL BE 24" X 30".
5. PROHIBITIVE SIGNS SHALL BE 24" SQUARE.
6. YELLOW SERIES WARNING SIGNS SHALL BE 30" X 30" DIAMOND. ALL OTHER WARNING SIGNS SHALL BE STANDARD MUTCD SIGNS. GUIDE SIGNS SHALL BE STANDARD MUTCD SIGNS.
7. SCHOOL SIGNS (PENTAGONAL AND DIAMOND) SHALL BE 30" X 30" EXCEPT SCHOOL SPEED LIMIT 20 MPH SIGNS WHICH SHALL BE 24" X 48".
8. STREET NAME SIGNS SHALL BE ON 9" X 30" OR 36" BLADES. BLADES SHALL BE 0.080" ANODIZED ALUMINUM WITH 1 1/2" RADIUS CORNERS, SINGLE SIDED, AND DRILLED FOR BACK TO BACK INSTALLATION ON SQUARE POSTS. BLADES SHALL BE PRISMATIC GRADE GREEN WITH WHITE LETTERS (WHITE SIGN W/GREEN LETTERS FOR PRIVATE STREETS). LETTERS, INCLUDING PREFIXES, ARE 6" HIGH AND SUFFIXES AND BLOCK NUMBERS ARE 3" HIGH. FOR BACK-TO-BACK INSTALLATION, USE DRIVE RIVETS TO ATTACH TO POSTS. PVC SPACERS W/ SIGNMATE RIVETS SHALL BE USED. ALL STREET NAME SIGNS SHALL BE INSTALLED WITH ARTERIAL STREET ON TOP AND SIDE STREET BELOW.
9. ALL SIGNS TO BE INSTALLED ON A TRAFFIC SIGNAL MAST ARM SHALL BE AS INDICATED ON PLANS OR AS DIRECTED BY ENGINEERING DEPARTMENT.


STRIPING \ PAVEMENT MARKERS
SIGNS

CITY OF MANSFIELD
ENGINEERING DEPARTMENT


PAVING

DATE:
APR. 2021


SHEET NO.
P-8



INLET PLAN




INLET ELEVATION




SECTION B-B


STANDARD CURB INLET DETAIL




THROAT DETAIL



RECESSED CURB INLET PLAN




SECTION F-F
INLET MID BOX STIFFENER BEAM
FOR 15', 20' & LARGER INLETS




GENERAL NOTES:

- ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENTS NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
- ALL CONCRETE SHALL BE CLASS "C", (6 SACK, 3600 PSI) (702.3.4.2 (a)). AGGREGATE SHALL BE 100% CRUSHED ANGULAR STONE (1" MAX). ALL CONCRETE PLACED SHALL CONTAIN SUFFICIENT AIR ENTRAINING AGENT TO YIELD 5% AIR CONTENT. ALL OTHER ADMIXTURES SHALL REQUIRE THE PERMISSION OF THE ENGINEERING DEPARTMENT.
- ON CONCRETE STREETS ALL INLETS SHALL BE SEPARATED FROM THE PAVEMENT AND CURB BY BLOCKING OUT AROUND INLETS AS SHOWN.
- ALL REINFORCING STEEL SHALL BE DEFORMED BARS (ASTM A-615 GRADE 60). REINFORCING STEEL SHALL BE PLACED WITH A MINIMUM OF 1-1/2" COVER.
- WHERE REINFORCING BARS ARE SPICED, A MINIMUM 30 DIAMETER LAP SHALL BE USED. MANUFACTURED BENDS OR FACTORY MADE "L" BARS SHALL BE USED IN ALL CORNERS, AND SHALL BE LONG ENOUGH TO PERMIT A MINIMUM OF A 30 DIAMETER SPLICE.
- INLETS LARGER THAN 10' SHALL HAVE TWO (2) LIDS. ONE TO BE LOCATED OVER OUTFALL AND THE OTHER LOCATED ON THE OPPOSITE SIDE OF THE STIFFENER BEAM.
- COVER IS A STANDARD CAST IRON LID AND RING WITH AN ATTACHED CHAIN EMBEDDED IN CONCRETE (BASS & HAYS 226).
- PRE-CAST INLETS WILL NOT BE PERMITTED.
- TOP AND THROAT TO BE PLACED MONOLITHICALLY.



STEP DETAILS




INSTALLATION

NOTE:

- INLET AND STORM DRAIN STEPS SHALL BE AS MANUFACTURED BY M.A. INDUSTRIES, INC. OF PEACHTREE CITY, GA. OR APPROVED EQUAL. STEPS SHALL REQUIRE A STEEL REINFORCING BAR AS SHOWN IN DETAIL.
- STEPS SHALL BE PLACED IN ALL INLETS OR STORM VAULTS WHERE THE DIMENSION FROM THE FLOW LINE TO THE TOP OF THE MANHOLE LID MEETS OR EXCEEDS 5'.
- STEPS SHALL BE PLACED WITH A MAXIMUM VERTICAL SEPARATION OF 16".

INLET STEP DETAIL

CURB INLET DETAILS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
STORM DRAIN	DATE: APR. 2021	SHEET NO. SD-1



NOTE:
REINFORCING #5 BARS
@ 6" CENTERS EACH WAY
HOOKED EACH END


PLAN
N.T.S.

#5 BARS @ 6" CENTERS
EACH WAY HOOKED EA. END

#4 BARS @ 18"
CENTERS VERTICAL

#4 BARS @ 12" CENTERS
HORIZONTAL

DIMENSIONS FOR SQUARE MANHOLES				
DIMENSION	MANHOLE WIDTH			
	4'	5'	6'	
A	8"	8"	9"	
B	8"	8"	9"	
C	12"	18"	24"	



SECTION A-A
N.T.S.

STD. MANHOLE RING & COVER (BASS & HAYS
VRM30 W/ "BASS" DESIGN)

MORTAR COVER
(EXTERIOR ONLY)
GRADE RINGS
AS REQUIRED
W/ APPROVED
EXTERIOR WRAP
SEAL

#4 BARS @ 18"
CENTERS VERTICAL
#4 BARS @ 12"
CENTERS HORIZONTAL


SLOPE 3/8" TO
DRAIN

U-SHAPED #5 BARS @ 9"
CENTERS EACH WAY
TO EXTEND INTO WALLS
TO ALLOW A MIN. 30 BAR
DIA. SPLICE.

SECTION B-B

STANDARD SQUARE MANHOLE
54" DIAMETER & SMALLER PIPES

N.T.S.




TYPICAL CORNER
DETAIL
(PLAN VIEW)

N.T.S.


GENERAL NOTES:

- ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
- ALL REINFORCING STEEL SHALL BE DEFORMED BARS (ASTM A-615 GRADE 60). REINFORCING STEEL SHALL BE PLACED WITH A MINIMUM OF 1-1/2" COVER FOR #5 BARS AND SMALLER.
- WHERE REINFORCING BARS ARE SPLICED, A MINIMUM 30 BAR DIAMETER LAP SPLICE SHALL BE USED. MANUFACTURED BENDS OR FACTORY MADE "L" BARS SHALL BE USED IN ALL CORNERS, AND SHALL BE LONG ENOUGH TO PERMIT A MINIMUM OF 30 BAR DIAMETER LAP SPLICE.
- ALL CONCRETE SHALL BE CLASS "C", (6 SACK, 3600 PSI) (702.3.4.2). AGGREGATE SHALL BE 100% CRUSHED ANGULAR STONE (1" MAX.). ALL CONCRETE PLACED SHALL CONTAIN SUFFICIENT AIR ENTRAINING AGENT TO YIELD 5% AIR CONTENT. ALL OTHER ADMIXTURES SHALL REQUIRE THE PERMISSION OF THE ENGINEERING DEPARTMENT.
- DROP INLET COVER (BASS & HAYS 226) LID SHALL BE ATTACHED WITH A CHAIN EMBEDDED OR ANCHORED IN CONCRETE.
- PRE-CAST INLETS OR MANHOLES WILL NOT BE PERMITTED FOR PUBLIC USE.
- ALL DROP INLETS SHALL HAVE APRON.



SECTION D - D
N.T.S.


DIMENSIONS FOR DROP INLET				
INLET SIZE	A	B	C	T
2' X 2'	36"	24"	2'	6"
3' X 3'	48"	36"	3'	6"
4' X 4'	60"	48"	4'	6"



PLAN

DROP INLET
N.T.S.

NOTE:
ALL REINFORCING IN TOP
TO BE #5 BARS @ 6"
CENTERS



DROP INLET APRON

N.T.S.

* CHAMFER ALL EXPOSED EDGES 3/4"

* WARP APRON TO MATCH FLOWLINES OF INCOMING DITCHES


MANHOLE AND DROP INLET DETAILS

CITY OF MANSFIELD
STANDARD CONSTRUCTION DETAILS


STORM DRAIN

DATE:
APR. 2021

SHEET NO.
SD-2



N.T.S.



N.T.S.



1. ALL PUBLIC STORM DRAIN SHALL BE MINIMUM CLASS III RCP.
2. CULVERT PIPES FOR DRIVES MAY BE EITHER RCP OR HDPE.
3. BOX CULVERTS TO BE AS DESIGNED PER CONSTRUCTION PLANS AND SPECIFICATIONS.

TRENCH, COLLAR & MISC. DETAILS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
STORM DRAIN	DATE: APR. 2021	SHEET NO. SD-3

1. ALL CONCRETE SHALL BE CLASS "C" (6 SACK, 3600 PSI) (702.3.4.2).
AGGREGATE SHALL BE 100% CRUSHED ANGULAR STONE (1" MAX.). ALL CONCRET PLACED
SHALL CONTAIN SUFFICIENT AIR ENTRAINING AGENT TO YIELD 5% AIR CONTENT.
ALL OTHER AD MIXTURES SHALL REQUIRE THE PERMISSION OF THE ENGINEERING DEPARTMENT.
2. 3:1 SLOPE IS TYPICAL.

The technical drawings illustrate the design of a culvert structure with the following details:

- PLAN:** Shows the top-down view of the culvert. The total length is labeled as $"L"$ **. The inlet width is $1'-0"$. The inlet has an $8"$ offset. The culvert body has a width of $"W"$. The outlet has a $6"$ offset and a total length of $1' - 6"$.
- ELEVATION:** Shows the side profile of the culvert. The inlet height is $18"$. The culvert body has a height of $4"$. The outlet has a height of $6"$ OR LESS. The culvert body is labeled "CONC. RIP RAP CL. 'B'". A "JOINT AS REQUIRED" is indicated. The outlet has a height of $12"$ and a width of $1' - 6"$.
- END VIEW:** Shows the circular cross-section of the culvert. The diameter is labeled $"D"$. The width of the structure is labeled $"W"$ and $(D + 2t + 1.0)$.

N.T.S.


OPTION ONE

"D"	SLOPE	"T" *	"W" (MIN.)	"L"	"X"
18"	3:1	2-1/4"	2' 10-1/2"	5' 3-3/4"	1' - 9"
18"	4:1	2-1/4"	2' 10-1/2"	7' - 9"	3' - 0"
18"	6:1	2-1/4"	2' 10-1/2"	10' 1-1/2"	3' - 0"
21"	3:1	2-1/2"	3' - 2"	5' - 9"	1' 4-1/2"
21"	4:1	2-1/2"	3' - 2"	8' - 4"	2' - 6"
21"	6:1	2-1/2"	3' - 2"	11' - 0"	2' - 3"
24"	3:1	3"	3' - 6"	7' - 6"	3' - 0"
24"	4:1	3"	3' - 6"	8' - 0"	2' - 0"
24"	6:1	3"	3' - 6"	12' - 0"	3' - 0"
27"	3:1	3-1/4"	3' 9-1/2"	7' 10-1/2"	2' 7-1/2"
27"	4:1	3-1/4"	3' 9-1/2"	10' - 0"	3' - 0"
27"	6:1	3-1/4"	3' 9-1/2"	15' - 0"	4' - 6"
30"	3:1	3-1/2"	4' - 1"	8' - 3"	2' - 3"
30"	4:1	3-1/2"	4' - 1"	10' - 6"	2' - 6"
30"	6:1	3-1/2"	4' - 1"	15' - 9"	3' - 9"

N.T.S.
OPTION TWO


"D"	SLOPE	"W"	"L"
18"	3:1	2'-6"	4'6-3/4"
18"	4:1	2'-6"	5'-9"
18"	6:1	2'-6"	8'1-1/2"
21"	3:1	2'-9"	5'4-1/2"
21"	4:1	2'-9"	6'-10"
21"	6:1	2'-9"	9'-9"
24"	3:1	3'-0"	6'-3"
24"	4:1	3'-0"	8'-0"
24"	6:1	3'-0"	11'-6"
27"	3:1	3'-3"	7'0-3/4"
27"	4:1	3'-3"	9'-1"
27"	6:1	3'-3"	13'1-1/2"
30"	3:1	3'-6"	7'10-1/2"
30"	4:1	3'-6"	10'-2"
30"	6:1	3'-6"	14'-9"

TYPE "P" HEADWALLS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
STORM DRAIN	DATE: APR. 2021	SHEET NO. SD-5




3/4" AND 1" WATER SERVICE DETAIL

N.T.S. (SEE NOTE 15)



1 1/2" AND 2" WATER SERVICE DETAIL

N.T.S. (SEE NOTE 16)



WATER MAIN PIPE TYPICAL EMBEDMENT DETAIL


N.T.S.

NOTE:

AT EVERY 100' INTERVAL ALONG TRENCH, DELETE BEDDING AND EMBEDMENT FOR 6' ALONG TRENCH. BACKFILL WITH COMPACTED CLAY SOILS OR FLOWABLE FILL TO DISCOURAGE WATER MOVEMENT DOWN TRENCH.

GENERAL NOTES:

- ALL CONSTRUCTION MATERIALS, METHODS, AND PLACEMENTS NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION, UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
- ALL WATER MAINS TO BE P.V.C. AWWA C-900, CLASS 150, DR-18 INSTALLED W/METALLIC MARKER TAPE LABELED "WATERLINE BELOW".
- BEVELED END OF PIPE WILL BE REMOVED WHEN USED IN MJ FITTING.
- ALL FITTINGS TO BE MJ UNLESS OTHERWISE NOTED. ALL VERTICAL BENDS TO BE RESTRAINED W/RETAINER GLANDS. HORIZONTAL BENDS OR FITTINGS TO BE RESTRAINED AS NEEDED PER ENGINEER/INSPECTOR.
- ALL 10" AND SMALLER WATER MAINS WILL BE HELD TO A MINIMUM COVER OF 42" UNLESS OTHERWISE BE SET BY THE ENGINEERING DEPARTMENT. 12" MAINS AND LARGER SHALL FOLLOW PLAN GRADE & PROFILE OF APPROVED CONSTRUCTION PLAN.
- SERVICE LOCATION SHALL BE STAKED BY SURVEYOR PRIOR TO THE INSTALLATION OF ANY WATER SERVICES, SEWER SERVICES, AND/OR METER BOXES.
- STORAGE: P.V.C. WATER PIPE IS ALLOWED TO BE STORED A MAXIMUM OF SIX (6) MONTHS WITHOUT COVER. THEREAFTER ALL PIPES SHOULD BE COVERED OR KEPT AWAY FROM SUN LIGHT AND PROTECTED FROM OTHER ELEMENTS.
- ALL IRON FITTINGS, INCLUDING FIRE HYDRANTS AND VALVES, SHALL BE POLY WRAPPED.
- EPOXY COATED TAPPING SADDLES SHALL BE USED. ALL SADDLES WILL HAVE DOUBLE STAINLESS STEEL STRAP. GASKET ON SADDLE TO BE FLAT, NO O-RINGS WILL BE PERMITTED. O.D. OF SADDLE SHALL NOT BE LARGER THAN O.D. OF PIPE. SADDLE MUST BE POLY-WRAPPED.
- ALL TAPS LARGER THAN 2" WILL BE MADE USING TAPPING SLEEVES, NOT SADDLES.
- TAPS WILL BE A MINIMUM OF 2' APART WITH TAPS NO CLOSER THAN 1' TO END OF PIPE. CUTTER FOR TAPS TO BE DOUBLE SLOTTED TYPE.
- IT IS THE RESPONSIBILITY OF THE DEVELOPER TO FURNISH AND INSTALL METER BOXES AS APPROVED BY THE ENGINEERING DEPARTMENT.
- METER BOXES WILL NOT BE PERMITTED IN DRIVEWAYS OR SIDEWALKS EXCEPT FOR COMMERCIAL BUILDING METERS AS APPROVED BY ENGINEERING DEPARTMENT. WHEN METER IS ALLOWED IN CONCRETE A TRAFFIC RATED BOX SHALL BE USED AND BOLLARDS TO BE PLACED AROUND METER FOR PROTECTION WHERE DIRECTED BY ENGINEER.
- METER BOXES SHALL HAVE A 2' MIN. SPACING FROM CURBS, DRIVEWAYS, MAIL BOXES, ETC.
- ALL 3/4" WATER SERVICES SHALL BE MADE BY USING 1" CORPORATION STOP, 1" SADDLE, 1" COPPER, AND 1" X 3/4" ANGLE CURB STOP.
- 1 1/2" WATER SERVICES SHALL BE MADE BY USING ALL 2" PARTS. THE 1 1/2" METER WILL BE SET ON A 2" ANGLE CURB STOP.
- ALL TAPPING VALVES SHALL BE BLOCKED PRIOR TO MOUNTING TAPPING MACHINE.
- SIZE ON SIZE TAPS SHALL NOT BE PERMITTED ON AC PIPE.
- SEE SHEET MS-1 AND MS-2 FOR APPROVED PARTS LIST.
- ALL WATER SERVICES SHALL HAVE NO JOINTS OR SPLICES UNDER PAVEMENT.



SERVICE LOCATION DETAIL

N.T.S.

WATER SERVICE, GENERAL NOTES, & TRENCH DETAILS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
WATER	DATE: APR. 2021	SHEET NO. W-1



1. MARKERS TO BE INSTALLED IN UNDEVELOPED AREAS OR AS INDICATED ON PLANS OR AS DIRECTED BY INSPECTOR.
2. MARKERS MUST BE PURCHASED FROM UTILITY DEPARTMENT. 817-728-3618.



- * CLASS B (4 SACK, 2000 PSI)


1. THRUST BLOCKS SHALL BE PLACED OR FORMED IN SUCH POSITION THAT ALL BOLTS REMAIN ACCESSIBLE.
2. ALL BLOCKING SHALL BE PLACED AGAINST UNDISTURBED FIRM TRENCH WALL.
3. BLOCKING AREAS SHOWN ABOVE ARE BASED ON 150 PSI PIPE PRESSURE AND MINIMUM SOIL BEARING OF 2000#/S.F.
4. ALL FITTINGS TO BE MJ UNLESS OTHERWISE NOTED. ALL VERTICAL BENDS TO BE RESTRAINED W/RETAINER GLANDS. HORIZONTAL FITTINGS TO BE RESTRAINED AS NEEDED PER ENGINEER OR INSPECTOR.



1. ALL VALVES TO BE RESILIENT SEAT GATE VALVES WITH NON-RIISING STEMS, COUNTER- CLOCKWISE OPENING.
2. VALVE STEM EXTENSIONS WITH ROCK GUARDS SHALL BE INSTALLED WHERE NECESSARY TO PLACE OPERATING NUT NOT MORE THAN 36" BELOW FINISHED GRADE. EXTENSIONS SHALL BE PAINTED OR COATED TO PREVENT RUST.
3. ALL VALVES SHALL HAVE CONCRETE PAD. (SEC. A-A)

N.T.S.

GATE VALVE, BLOCKING, MARKER, & LOWERING DETAILS		
CITY OF MANSFIELD STANDARD CONSTRUCTION DETAILS		
WATER	DATE: APR. 2021	SHEET NO. W-2




BLOW OFF VALVE DETAIL

N.T.S.

NOTES:


1. MUST BE DISCHARGED NEAR\TOWARD STORM SEWER, BRIDGE OR CULVERT.
2. USE APPROPRIATE BEND TO MAKE DISCHARGE END HORIZONTAL.
3. ALL FITTINGS SHALL BE RETAINED & DISCHARGE END SHALL BE CLOSED W/MJ PLUG.



COVER DETAIL

N.T.S.

NOTE: COMBINATION AIR AND VACUUM RELEASE VALVES LARGER THAN 2" TO BE SPECIFIED IN CONSTRUCTION PLANS BY DESIGN ENGINEER.




NOTES:

1. COMBINATION AIR AND VACUUM-AIR RELEASE VALVE A.R.I. - D040P OR AWWA APPROVED EQUAL.
2. USE OF OFFSET OR NON-OFFSET TO BE DETERMINED BY ENGINEER PER FIELD CONDITION.

2" OFFSET AIR & VACUUM RELEASE VALVE INSTALLATION

N.T.S.




NOTES:

1. COMBINATION AIR AND VACUUM-AIR RELEASE VALVE A.R.I. - D040P OR AWWA APPROVED EQUAL.
2. USE OF OFFSET OR NON-OFFSET TO BE DETERMINED BY ENGINEER PER FIELD CONDITION.

1" OFFSET AIR AND VACUUM RELEASE VALVE INSTALLATION


N.T.S.

BLOW OFF & AIR RELEASE VALVE DETAILS		
CITY OF MANSFIELD STANDARD CONSTRUCTION DETAILS		
WATER	DATE: APR. 2021	SHEET NO. W-3



STANDARD FIRE HYDRANT DETAIL

N.T.S.




WATER APPURTENANCE MARKERS

NOTES:

1. EACH WATER SYSTEM VALVE LOCATED ADJACENT TO OR IN A CITY STREET FIRE LANE SHALL RECEIVE A MARKER PLACED ON THE CURB AS CLOSE AS POSSIBLE TO THE VALVE. VALVES TO BE MARKED BY SAWING A "V" IN FACE OF CURB ADJACENT TO VALVE BOX. VALVES NOT IN STREET MARKED WITH UPSIDE-DOWN "V".
2. EACH LOCATION OF A FIRE HYDRANT SHALL RECEIVE A BLUE REFLECTORIZED MARKER LOCATED IN THE CENTER OF ANY STREET TO WHICH IT IS ADJACENT (2 FOR HYDRANTS ON STREET CORNERS).
3. ALL BLUE FIRE HYDRANT MARKERS SHALL BE A CUBE CORNER TYPE REFLEX REFLECTOR MOLDED OF OPTIC GRADE PLASTIC, WITH A HOUSING OF HIGH IMPACT ABS PLASTIC, WITH A FILLER OF INERT THERMOSETTING RESINS. APEX UNIVERSAL, INC. TYPE: BB TWO WAY BLUE.

FIRE HYDRANT NOTES:

1. CENTER OF F.H. BARREL SHALL BE NOT LESS THAN 2.5' OR MORE THAN 3.5' FROM BACK OF CURB OR EDGE OF PAVEMENT, UNLESS OTHERWISE APPROVED BY THE ENGINEERING DEPARTMENT. HYDRANT TO BE LOCATED NO CLOSER THAN 3' FROM ANY OTHER OBJECTS, MEASURED FROM CENTER OF OPERATING NUT.
2. ON PRIVATE CONTRACTS, THE DEVELOPER'S ENGINEER WILL STAKE F.H. HORIZONTAL LOCATION AND FLANGE ELEVATION.
3. FIRE HYDRANTS SHALL BE INSTALLED PRIMED ONLY, PAINTED AFTER INSTALLATION. PRIMER COLOR "ALUMINUM".
4. FIRE HYDRANTS SHALL BE COATED WITH HYDRANT HYDE, FLYNT, OR TENEMEC BRAND PAINTS. THE COLOR SHALL BE ALUMINUM.
5. HYDRANT LEADS OR FIRE LINES IN EXCESS OF 200' REQUIRE DOUBLE-CHECK ASSEMBLY AT MAIN (SEE SHEET W-6).
6. ALL HYDRANT EXTENSIONS SHALL HAVE BREAKAWAY FLANGE AND STEM COUPLING. IF EXTENSIONS ARE USED, BREAKAWAY FLANGE MUST BE MOVED TO TOP.
7. BLOCKING OF FIRE HYDRANT SHALL BE REQUIRED FOR EXTENSIONS ACROSS STREETS FROM MAINS OF LEADS LONGER THAN ONE JOINT OF PIPE. LAST JOINT OF PIPE CONNECTING TO HYDRANT MUST BE A FULL JOINT.
8. LOWER BARREL ON FIRE HYDRANT SHALL NOT EXCEED 7'-0". IF NECESSARY, RETAINED BENDS MAY BE USED TO ACHIEVE GRADE NEEDED WITHOUT EXCEEDING 7'-0" LOWER BARREL HEIGHT. ALL PIPING TO BE DUCTILE IRON.
9. PIPE WITH RETAINER GLANDS WILL ONLY BE PERMITTED FOR LEADS THAT EXCEED 36".
10. HYDRANT BARREL TO BE POLY WRAPPED.




NOTE:

REMOVE COPPER AND CORPORATION STOP FROM MAIN AND INSTALL PLUG IN SADDLE AND POLY WRAP UPON CONSTRUCTION COMPLETION.

TEMPORARY FLUSH VALVE/SAMPLE POINT

N.T.S.



NOTE:

FILL VOIDS BETWEEN ENCASEMENT PIPE AND THE SURROUNDING GROUND COMPLETELY WITH GROUT.

BORE NOTES:


1. ALL BORES SHALL BE CASED. (TYP. 2 NOMINAL SIZES LARGER THAN CARRIER).
2. CASING PIPE SHALL BE COATED INSIDE AND OUTSIDE WITH BITUMINOUS COATING.
3. VOIDS OUTSIDE OF CASING PIPES SHALL BE GROUT FILLED.
4. SEE SHEET MS-2 FOR APPROVED SPACERS.
5. SPACERS TO BE INSTALLED PER MANUFACTURER'S SPECIFICATION.
6. MINIMUM CASING THICKNESS 3/16".

BORE DETAIL

N.T.S.

FIRE HYDRANT, TEMPORARY FLUSH VALVE, & BORE DETAILS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
WATER	DATE: APR. 2021	SHEET NO. W-4

1. ALL VAULTS W/METER OR BACKFLOW PREVENTERS SHALL BE PRECAST AND DELIVERED WITH ALL INTERNAL PIPING AND PARTS COMPLETE. METER AND BACKFLOW PREVENTER TO BE IN SEPARATE VAULTS.
2. ALL PIPES MUST BE DUCTILE IRON & ALL FITTINGS MUST BE FLANGED IN VAULT.
3. CONCRETE SHALL BE CLASS "F" WITH DESIGN STRENGTH OF 4200 PSI @ 28 DAYS (702.3.4.2). UNIT IS OF MONOLITHIC CONSTRUCTION AT FLOOR AND FIRST STAGE OF WALL WITH SECTIONAL RISER TO REQUIRED DEPTH.
4. GRADE 60 REINFORCED, STEEL REBAR CONFORMING TO ASTM A615 ON REQUIRED CENTERS OR EQUAL.
5. 1/4"ALUMINUM DIAMOND PLATE COVER WITH EXTRUDED ALUMINUM FRAME. HATCH TO BE FURNISHED WITH 316 STAINLESS STEEL SNAP LOCK & STAINLESS HINGES TO BE CENTERED OVER METER.
6. MODEL NUMBER IS FOR PARK EQUIPMENT COMPANY, MODEL IS DMC-MF. UNITS BY OTHER MANUFACTURERS MUST BE SUBMITTED TO BE APPROVED AS EQUALS.



Technical drawing of a 12-inch water valve assembly in plan view. The drawing shows a central valve assembly with two gate valves and a central check valve, all connected by galvanized steel pipe. The assembly is supported by a galvanized steel pipe support. The entire assembly is housed within a concrete structure with a 6-inch gravel bed at the bottom. The concrete structure has a 6-inch thick wall and a 6-inch thick top. The assembly is surrounded by a 6-inch gravel bed. The drawing includes dimensions for the assembly, including a 12-inch minimum clearance for the gate valves and a 12-inch clearance for the central check valve. The drawing also shows a 12x12 inch sump with a cast iron grate at the bottom. The drawing is labeled with 'FLOW' arrows indicating the direction of water flow. The drawing is titled '12" WATER VALVE' and 'PLAN'.

Labels and dimensions in the drawing include:

- 6"
- 12"
- 12" MIN.
- 6"
- 22"
- H1
- FLOW
- TAPER WALL
- JOINTS SEALED WATERTIGHT w/ RAMNEK GASKET
- DUCTILE IRON (TYPICAL)
- GALV STEEL PIPE SUPPORT
- 6" GRAVEL BED
- 12"x12" SUMP WITH CAST IRON GRATE
- L1

ELEVATION


3", 4", & 6" DOMESTIC METER

APPROVED GATE VALVES:
MUELLER, KENNEDY, CLOW
WATEROUS, M & H

3" & LARGER WATER SERVICE DETAILS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
WATER	DATE: APR. 2021	SHEET N W-5


GENERAL NOTES:

1. ALL BACKFLOW PREVENTER VAULTS SHALL BE PRECAST AND DELIVERED WITH ALL INTERNAL PIPING AND PARTS COMPLETE.
2. ALL PIPE MUST BE DUCTILE IRON & ALL FITTINGS MUST BE FLANGED IN VAULT.
3. CONCRETE SHALL BE CLASS "F" WITH DESIGN STRENGTH OF 4200 PSI @ 28 DAYS (702.3.4.2). UNIT IS OF MONOLITHIC CONSTRUCTION AT FLOOR AND FIRST STAGE OF WALL WITH SECTIONAL RISER TO REQUIRED DEPTH.
4. GRADE 60 REINFORCED, STEEL REBAR CONFORMING TO ASTM A615 ON REQUIRED CENTERS OR EQUAL.
5. 1/4" ALUMINUM DIAMOND PLATE COVER WITH EXTRUDED ALUMINUM FRAME. HATCH TO BE FURNISHED WITH 316 STAINLESS STEEL SNAP LOCK & STAINLESS HINGES.
6. BACKFLOW ASSEMBLY SHALL BE FACTORY ASSEMBLED IN VAULT & HYDROSTATICALLY TESTED PRIOR TO DELIVERY.
7. MODEL NUMBERS ARE FOR PARK EQUIPMENT COMPANY, MODELS ARE DDBP-MF (FIRE SERVICE) OR BP-M (DOMESTIC). UNITS BY OTHER MANUFACTURERS MUST BE SUBMITTED TO BE APPROVED AS EQUALS.




MODEL	SIZE	L1	W1	H1	ALUM. HATCH	WEIGHT LBS
BP-MF3	3"	6'-0"	3'-6"	5'-0"	30X36	6,000
BP-MF4	4"	6'-0"	3'-6"	5'-0"	30X36	6,000
BP-MF6	6"	6'-0"	5'-0"	5'-0"	30X48	9,000
BP-MF8	8"	8'-8"	5'-0"	6'-0"	30X48	15,000
BP-MF10	10"	9'-0"	6'-0"	6'-6"	30X48	18,000

PLAN VIEW




ELEVATION

DOMESTIC DOUBLE-CHECK ASSEMBLY



PLAN VIEW

MODEL	SIZE	L1	W1	H1	WEIGHT LBS
DDBP-MF4	4"	6'-0"	5'-0"	6'-0"	9,000
DDBP-MF6	6"	6'-0"	5'-0"	6'-0"	9,200
DDBP-MF8	8"	8'-8"	5'-0"	6'-0"	15,000
DDBP-MF10	10"	9'-0"	6'-0"	7'-0"	18,000



ELEVATION


FIRE SERVICE DETECTOR
DOUBLE-CHECK ASSEMBLY

3" & LARGER BACKFLOW
PREVENTION DEVICE DETAILS
CITY OF MANSFIELD
STANDARD CONSTRUCTION DETAILS



WATER

DATE:
APR. 2021


SHEET NO.
W-6




CLEAN - OUT
N.T.S.





CLEANOUT COVER PAD DETAIL
N.T.S.




MANHOLE MARKER
N.T.S.



SECTION "A - A"
N.T.S.




MANHOLE PAD DETAIL
N.T.S.




CLEANOUT COVER
N.T.S.


NOTE:
THIS DETAIL FOR CLEAN
OUTS NOT IN PAVEMENT.



**DROP CONNECTIONS FOR
SANITARY SEWER MANHOLE**
N.T.S.



CAST IN PLACE MANHOLE
N.T.S.




PRECAST CONCRETE MANHOLE
N.T.S.

GENERAL NOTES:

1. ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
2. RING AND COVER SHALL BE DOMESTIC CASTING ONLY. (BASS & HAYS VRM 30 WITH CITY LOGO). CAST IN PLACE MANHOLE OR WEIGHTED DESIGNED CONE WITH BOLT-DOWN, WATER-TIGHT RING AND COVER TO BE USED IN FLOOD-PRONE AREA AND MUST BE ANCHORED INTO CONE.
3. MANHOLE MARKERS SHALL BE INSTALLED IN ALL UNDEVELOPED AREAS.
4. MANHOLES IN DEVELOPED AREAS THAT ARE NOT IN PAVEMENT SHALL HAVE A 4'x4'x6" CONCRETE PAD.
5. MANHOLES SHALL BE PLACED MONOLITHICALLY WITH STREET. IF A BLOCK OUT IS NEEDED INSPECTOR WILL PRE-APPROVE SIZE & SHAPE OF BLOCK OUT.
6. INVERTS FOR CAST-IN-PLACE MANHOLES SHALL BE MADE BY PLACING PIPE CONTINUOUSLY THROUGH MANHOLES AND CUTTING OUT THE TOP OF THE PIPE. A MINIMAL AMOUNT OF CONCRETE INVERT BETWEEN PIPE ENDS WILL BE PERMITTED.
7. CONCRETE FOR MANHOLES TO BE CLASS "F" (6.5 SACK, 4200 PSI) PER NCTCOG SPECIFICATIONS 702.3.4.2. ALL CONCRETE SHALL CONTAIN SUFFICIENT AIR ENTRAINING AGENT TO YIELD 5% AIR CONTENT.
8. INTERSECTING PIPES WITH FLOWLINE ELEVATION DIFFERENCES GREATER THAN 2' MUST USE DROP MANHOLE.
9. MANHOLE EXTERIOR JOINTS AND GRADE RINGS SHALL BE SEALED WITH CONSEAL-CONWRAP OR APPROVED EQUAL. MINIMUM WIDTH 12".

MANHOLE & CLEANOUT DETAILS		
CITY OF MANSFIELD STANDARD CONSTRUCTION DETAILS		
SANITARY SEWER	DATE: APR. 2021	SHEET NO. SS-1




NOTES:

1. RUBBER BOOTS WILL ONLY BE PERMITTED FOR CLAY OR CONCRETE TILE SERVICE PIPE AND MUST BE CONCRETE ENCASED.

STANDARD SEWER SERVICE CONNECTION

N.T.S. (PLUMBER CONNECTION OR CIP RECONSTRUCTION)




NOTE:

AT EVERY 100' INTERVAL ALONG TRENCH, DELETE BEDDING AND EMBEDMENT FOR 6' ALONG TRENCH. EMBED WITH CLASS "B" CONCRETE OR FLOWABLE FILL TO DISCOURAGE WATER MOVEMENT DOWN TRENCH.

SANITARY SEWER TYPICAL EMBEDMENT

N.T.S.




STANDARD SEWER SERVICE FOR NEW CONSTRUCTION

N.T.S.

GENERAL NOTES:

1. ALL CONSTRUCTION MATERIALS, METHODS AND PLACEMENT NOT DETAILED BELOW SHALL MEET OR EXCEED THE STANDARD SPECIFICATIONS OF THE NORTH CENTRAL TEXAS COUNCIL OF GOVERNMENTS, 5TH EDITION UNLESS SUPERSEDED BY CITY OF MANSFIELD STANDARD SPECIFICATIONS OR MATERIAL TESTING POLICIES.
2. WHERE COVER IS LESS THAN 3.5 FEET, SANITARY SEWER MAINS AND LATERALS SHALL BE CONCRETE ENCASED OR CAPPED (SEE SHEET M-1).
3. METALLIC TRACER/MARKER TAPE, GREEN IN COLOR AND MARKED "SANITARY SEWER", TO BE PLACED ALONG MAIN LINES & SERVICES ON TOP OF CRUSHED STONE EMBEDMENT.
4. SEE SHEET W-1 FOR SERVICE LOCATION.
5. SEE SHEET MS-2 FOR APPROVED MATERIAL LIST.



STANDARD DEEP SERVICE DETAIL FOR NEW CONSTRUCTION

N.T.S.

NOTES:

1. ROTATE TEE-WYE TO 45° MAX.
2. ONLY ONE 45° BEND WILL BE USED, 45° BEND MUST BE PLACED OUTSIDE OF PAVEMENT WHERE POSSIBLE.
3. CONCRETE ENCASE 45° BEND.

SERVICE & TRENCH DETAILS


CITY OF MANSFIELD

STANDARD CONSTRUCTION DETAILS


SANITARY SEWER

DATE:
APR. 2021

SHEET NO.
SS-2



**TYPICAL SECTION
ASPHALT PAVEMENT REPAIR**
N.T.S.




**TYPICAL SECTION
CONCRETE PAVEMENT REPAIR**
N.T.S.

GENERAL NOTES:


1. BACKFILL FOR OPEN CUTS IN EXISTING IMPROVED PAVED ROADWAYS SHALL BE MODIFIED FLOWABLE BACKFILL PER NCTCOG SPEC 504.2.3.5. NATIVE MATERIAL MAY BE PERMITTED IN LOWER PORTION OF DEEP TRENCHES AT INSPECTOR'S DISCRETION.
2. CONCRETE PAVEMENT REPLACEMENT SHALL BE IN A MINIMUM OF ONE HALF PANEL INCREMENTS.
3. REFER TO CITY OF MANSFIELD MATERIAL TESTING POLICIES FOR BACKFILL TESTING PROCEDURES.
4. TRENCH SAFETY: THE CONTRACTOR SHALL PROVIDE A TRENCH SAFETY PLAN WHICH SPECIFICALLY ADDRESSES AND IDENTIFIES THE TRENCHES TO BE MADE ON THIS PROJECT AND PROVIDES THE TRENCHING DETAILS TO PROVIDE A SAFE WORK PLACE IN ACCORDANCE WITH STATE LAW AND OSHA REGULATIONS. THE TRENCH SAFETY PLAN SHALL BEAR THE SEAL AND SIGNATURE OF A REGISTERED PROFESSIONAL ENGINEER LICENSED IN THE STATE OF TEXAS WITH EXPERIENCE IN PREPARATION OF TRENCH SAFETY SYSTEMS. THE PLAN SHALL INCLUDE ALL SOILS INVESTIGATION AND TEST DATA USED BY THE ENGINEER IN DEVELOPING THIS PLAN. THE CONTRACTOR SHALL CONDUCT HIS TRENCHING OPERATIONS IN ACCORDANCE WITH THIS PLAN. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DAILY INSPECTION AND ENFORCEMENT OF SUCH PLAN.
5. ALL "POTHOLE" MADE UNDER EXISTING PAVEMENT BY HYRO-EXCAVATION MUST BE BACKFILLED WITH FLOWABLE FILL PER 504.2.3.5. CORE HOLE IN PAVEMENT TO BE REPLACED WITH 6 SACK 4500 PSI CONCRETE.

PAVEMENT AND TRENCH BACKFILL DETAILS



NOTE:
THIS DETAIL SHALL APPLY
AS CALLED FOR IN THE
PLANS AT VARIOUS LOCATIONS.

CONCRETE ENCASEMENT
N.T.S.



PIPE CONCRETE CAP DETAIL
N.T.S.

TRENCH DETAILS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
MISCELLANEOUS	DATE: APR. 2021	SHEET NO. M-1

ITEM	MATERIAL	SPECIFICATION	MIN. PRESS. CLASS	SIZE RANGE	MANUFACTURER/ MODEL	NOTES
WATER						
Water Pipe	PVC	AWWA C-900	DR-18	4" - 48"		Blue
	PVC (MO)	AWWA C-909	150 PSI	6" - 12"		Use D.I. O.D., Blue
	Ductile Iron	AWWA C-150/151	250 PSI	16" - 36"		Pressure Class to be project specific
Service Saddles	Ductile Iron Body, Stainless Straps			1"	Smith Blair 315 Romac 101N	Epoxy Coated (AWWA C-550), Double Stainless Straps Flat Gasket - No O-rings, Controlled OD
					Ford FS 101 JCM 405	
				2"	Romac 202N Ford 202 FS	Epoxy Coated (AWWA C-550), Double Stainless Straps Flat Gasket - No O-rings, Controlled OD
					JCM 406 Smith Blair 317	
Gate Valves	Cast Iron	AWWA C-509		4" - 12"	M&H/Kennedy/Clow Mueller 2360	Non Rising Stem (NRS), Epoxy Coated (AWWA C-550) Open counter-clock-wise
					American Flow Control 2500	
	Ductile Iron	AWWA C-515		4" - 12"	M&H/Kennedy/Clow Mueller 2361	Non Rising Stem (NRS), Epoxy Coated (AWWA C-550) Open counter-clock-wise
					American Flow Control 2500	
Butterfly Valves		AWWA C-504	Project Specific	16" +	M&H/Kennedy/Clow Pratt Mueller Lineseal	Sealed, Gasketed & Lubed for Direct Bury Service Min. 450 ft-lb Overload Torque; Open counter-clock-wise Epoxy Coated Inside & Out (AWWA C-550)
Tapping Sleeves	Stainless Steel Body, Steel Flange				Smith Blair 662, 664 Powerseal 3490 JCM 432	Full Circle flat gasket - No O-ring Size on Size not permitted on AC Pipe
					Mueller H-304	
	Ductile Iron				Mueller H-615	
Hydrants	Cast & Ductile Iron	AWWA C-502		5-1/4"	Waterous Pacer Clow Medallion Mueller Super Centurian	Pent Nut, 4-1/2" Pumper Nozzle, Open Counter-clock-wise
Hydrant Paint	Aluminum				Hydrant Hyde, Flynt, Tnemec	Color: Aluminum
Meter Box	Plastic			3/4" & 1"	D 1200	In Grass – Lid OLSB
	Plastic Box			3/4" & 1"	1118-12	In Sidewalk - 1-piece lid - Fibrelyte lid w\ AMR bracket (Undermount)
	Plastic Box			1-1/2" & 2"	1527-12	All Locations - 1-piece lid - Fibrelyte lid w\ AMR bracket (Undermount)
Retainer Glands	Ductile Iron				EBAA Iron Megalug Romac Roma Grip Sigma One Lock Star Grip	EBAA uses special gasket
Corp. Stops	Brass (Lead Free)			1"	Ford F1000-4G Comp. Mueller H-15008	Male CC Thread x Comp.
				1"	AY McDonald 74701G	
				2"	Ford FB 1000-7G	
				2"	Mueller H-15013	
				2"	AY McDonald 74701G	
Angle Curb Stops	Brass (Lead Free)			1" x 3/4"	Ford KV43-342WG Mueller H-14258	Comp. x Meter Swivel Nut
				1" x 3/4"	AY McDonald 74602G	
				1"	Ford KV43-444WG Mueller H-14258	
				1"	AY McDonald 74602G	
				2"	Ford FV43-777WG -or- BFA43-777WG	Comp. x Meter Flange (Ground Key -or- Ball Valve)
				2"	Mueller H-14277 -or- B-24276	
				2"	AY McDonald BCSG	
Pipe Fittings	Cast Iron	AWWA C-110		16" +		Domestic & Foreign
	Ductile Iron	AWWA C-153		4" - 36"		Domestic & Foreign
Misc. Castings	Cast Iron			24" - 36" / 36" - 48"	Tyler 6850 Series EJ 8550 Series	Valve Boxes - 2 Piece Screw Type (Domestic Only) (w\City logo)

MATERIAL SPECIFICATIONS		
CITY OF MANSFIELD		
STANDARD CONSTRUCTION DETAILS		
MATERIALS	DATE: APR. 2021	SHEET NO. MS-1

ITEM	MATERIAL	SPECIFICATION	MIN. PRESS.	SIZE	MANUFACTURER/	NOTES
			CLASS	RANGE	MODEL	
SANITARY SEWER						
Sewer Pipe	PVC	ASTM D-3034	SDR-26	6" - 15"		All Piping to be Green Color
	PVC	ASTM D-2241	SDR-26			Pressure rated pipe for TCEQ Water/Wastewater Crossing Separation Exceptions
	PVC	ASTM F-679		18" +		
	PVC Open Profile	ASTM F-794		15" +		
	PVC Dual Wall Corrugated Profile	ASTM F 794, F 949		15" +		
Force Main Sewer Pipe	Green PVC	AWWA C-900	DR-18	4" - 48"		
Sewer Fittings	PVC	ASTM D-3034	SDR-35	6" - 24"	NAPCO - G-series	SDR-26 for Deep Cover (Greater than 20', Project Specific)
					Multi-Fitting - Trench Tough Plus	
End of Line Clean-out	Cast Iron				Bass & Hayes 339	
Service Clean-out Caps	Plastic (In Grass), Cast Iron (In Concrete)			4"	NDS 404; EJIW 404	
SS MH Ring & Cover	Cast Iron				Bass & Hayes VRM30	Domestic Only (with "Sanitary Sewer" lettering)
					Bass & Hayes VRM30WT	Water-Tight Applications
MISCELLANEOUS						
Casing Spacers	Plastic			6" - 12"	Raci F/G	
	Plastic			14" - 20"	Raci M/N	
	Plastic			24" - 30"	Raci E/H	
	Plastic or Stainless Steel			6" - 12"	PSI Ranger Midi or Model SG	
	Plastic or Stainless Steel			14" - 30"	PSI Ranger Maxi or Model SG	
STORM SEWER						
Storm Drain Pipe	Reinforced Concrete		Class III	18" +		All Public Installations
Inlet Ring & Cover	Cast Iron				Bass & Hayes #226	Domestic Only
Storm MH Ring & Cover	Cast Iron				Bass & Hayes VRM30	Domestic Only (with "Storm Sewer" lettering)
Drive Culverts	HDPE – OR – RCP			18" Minimum		For Residential and Commercial Drive Approaches on Roads w/ Bar Ditches. Type "P" headwalls required.

MATERIAL SPECIFICATIONS

CITY OF MANSFIELD
STANDARD CONSTRUCTION DETAILS

MATERIALS

DATE:
APR. 2021

SHEET NO.
MS–2